

# SAFETY DATA SHEET ( SDS )

Revision date: June- 14- 2018

## 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### 1.1 Identification of product

Product name : ULTRAIR AIRSOFT POWER GAS

Ref No. : 14571

UN/NA(PIN)No. UN1950

Applications :

### 1.2 Identification of supplier

ActionSportGames A/S

Bjergvangen 1 3060 Espergaerde . Denmark

Telephone: (45)8928 1888

Fax: (45)4919 3160

Emergency telephone : (45) 8928 1888

### 1.3 Area of application

For use in Gasoperated Air soft Guns

## 2 HAZARDS IDENTIFICATION

### 2.1 Classification of Substance or Mixture

Classification according to Regulation (EC) No 1272/2008(CLP)

: Extremely flammable gas ( H220)

### 2.2 Lable elements

Labeling according to Regulation(EC)No1272/2008( CLP)



Signal Words :

Danger

Hazard statements : Extremely flammable gas

Precautionary statements :

General : Keep out of the reach for children

Prevention : Keep away from heat / sparks /open flames / hot surfaces - No smoking

Leaking gas fire ; Do not extinguish ,unless leak can be stopped safely

Store : Store in a well ventilated place

### 2.3 Other Hazards

No additional information available

## 3 COMPOSITION / INFORMATION ON INGREDIENTS

Name	CAS no.	EINECS no.	Concentration %	Classification
Propane	74-98-6	200-827-9	90%	Simple Asphy
Butane	106-97-8	203-448-7	10%	Flam. Gas 1 H220
Butane(containing $\geq 0.1\%$ butadiene( 230 - 450 - 8 ) May cause frostbite				Liquefied Gas , H280

## 4 FIRST AID MEASURES

### 4.1 Inhalation

Immediately remove to fresh air in case of accidental inhalation of vapours.

Seek medical advice as soon as possible

### 4.2 Skin Contact

Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

Seek medical advice as soon as possible if irritation or frostbite occurs

### 4.3 Eye Contact

For contact with the liquid, immediately flush eyes thoroughly with warm water for at least 15 minutes.

Hold the eyelids open and away from eyeballs to ensure that all surfaces are flushed thoroughly.

Seek medical attention immediately

### 4.4 Ingestion

Unlikely route of exposure. This product is a gas at normal temperature and pressure.

## 5 **FIRE FIGHTING MEASURES**

- 5.1 Extinguishing media  
CO<sub>2</sub>, dry chemicals, water spray or fog.
- 5.2 Special fire fighting procedures  
Evacuate all personnel from danger area. Remove ignition sources if without risk.  
Use water to disperse vapours. Remove all cylinders from area of fire if without risk.
- 5.3 Unusual fire and explosion hazards  
Possible risk of can rupture when exposed to fire/high temperatures.
- 5.4 Hazardous Decomposition Products  
Fire or high temperatures can create carbon monoxide and/or carbon dioxide

## 6 **ACCIDENTAL RELEASE MEASURES**

- 6.1 Steps to be taken in case of release or spill  
Flammable liquid and gas under pressure forms explosive mixtures with air.  
Immediately evacuate all personnel from danger area. Remove all sources of ignition if without risk.  
Reduce vapors with fog or fine water spray. Ventilate area or remove cylinders to well ventilated areas.
- 6.2 Waste disposal method  
Prevent waste from contaminating the surrounding environment. Keep personnel away.  
Discard any product, residue, disposable container in any environmentally acceptable manner, in full compliance with national, state, and local regulations.

## 7 **HANDLING AND STORAGE**

- 7.1 Handling  
The gas may explode when heated or on contact with fire and static electricity.  
Therefore, it is extremely important to keep it from any source of ignition.  
Avoid contact with skin, eyes and clothing.
- 7.2 Storage  
Store in cool, dry place away from all sources of heat including direct sunlight.

When possible, use appropriate container.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Respiratory protection  
Make sure that the ventilation is good in the place of use. Self-contained breathing apparatus is needed only when the concentration exceeds the exposure limits or when working during a large gas leak.
- 8.2 Hand protection  
To prevent frostbites, protecting oil and cold resistant gloves should be worn when using this product.
- 8.3 Skin and Body protection  
Overall or long-sleeved work clothing, and closed-in shoes or safety footwear.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

- |     |                                       |  |
|-----|---------------------------------------|--|
| 9.1 | Molecular Weight                      | 44.50  |
| 9.2 | Specific Gravity (50/60°F)            | 0.49 to 0.57(liquid)   |
| 9.3 | Vapor pressure at 20 Deg. Celsius     | 107 to 730 kpag ( 1 bar = 100 kpag )   |
| 9.4 | Boiling point (Celcius)               | - 42   |
| 9.5 | Dew Point (Celsius)                   | -39.40   |
| 9.6 | Latent heat of vaporization (Kcal/kg) | 102.00   |
| 9.7 | Appearance, odor and state            | Colorless gas at normal temperature and pressure, faintly disagreeable odor. |
| 9.8 | Low Flammability Limit                | 1.9% in air  |
| 9.9 | Upper Flammability Limit              | 9.5% in air  |
|     | Flash point ( Celcius )               | - 41   |

## 10 STABILITY AND REACTIVITY

- 10.1 Conditions to avoid  
The gas is normally stored under pressure in liquid form. It is fairly stable under normal temperature (below 50 Celcius) and normal pressure (1 atm) As the gas temperature and pressure change, the gas will react accordingly. Thus, possible dangers may occur.
- 10.2 Materials to avoid  
May explode if mixed with oxidizer, nickel carbonyl or oxygen.

- 10.3 Hazardous decomposition products  
Carbon monoxide

11 **TOXICOLOGICAL INFORMATION**

- 11.1 Acute toxicity  
In theory, LPG is a tranquilizer of the human central nervous system. Therefore, if it comes in direct contact with humans it may be potentially harmful.
- 11.2 Irritation and corrosion  
INHALED: irritation of the respiratory tract. At moderate exposures, subject is likely to have headaches or experience dizziness. At high exposure, lack of oxygen may result in consciousness and respiratory arrest.  
EYE: May cause irritation, with a possibility of freezing due to rapid evaporation.  
SKIN: Excessive and prolonged contact with the liquid can cause skin irritation and frostbite due to rapid evaporation.

12 **ECOLOGICAL INFORMATION**

No adverse ecological effects expected. Propane does not contain any Class I or Class II ozone-depleting chemicals. Propane is not listed as a marine pollutant.

13 **DISPOSAL CONSIDERATIONS**

Do not puncture or incinerate even when empty.  
Dispose of in accordance with local authority requirements.

14 **TRANSPORT INFORMATION**

- 14.1 Land Transport  
ADR/RID                      RID  
ADR/RID labels              dg-placard class 2.1
- 14.2 Description of the goods :      UN1950
- 14.3 Sea Transport  
UN No. SEA :                      UN1950

IMDG CLASS : 2.1 Limited Quantity  
IMDG PACK GR. :  
EmS No. F - D , S - U  
MFAG TABLE No. 620  
Description of the goods : UN1950

15

**REGULATORY INFORMATION**

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable national, state and local regulations.

16

**OTHER INFORMATION**

This SDS was prepared and is to be used only for this product , If the products is used as a component in another products , this SDS information may not be applicable, The responsibility of the use of the product lies with the customer.